

Steel fireplace insert Spartherm Premium V-2R-55h, with corner glass in the right



Product code: Z2SPA-1067231
Category: Fireplaces > Steel fireplaces

PRICE : €6,000.00

About the product

Manufacturer: Spartherm
Height, mm: 1561
Width, mm: 642
Depth, mm: 597
Efficiency class: A+
Efficiency: 80,00
Made of: plieno
Fuel type: malkos
Chimney diameter, mm: 180
Shape of glass: L formos
Item type: pakeliamomis duralėmis
Warranty, year: 60

Description

Top materials, high-quality workmanship, great function and a long product life – that is the kind of quality Spartherm represent and you can rely on. State-of-the-art technology, great efficiency and optimised energy usage – various innovations allow us to meet all demands made of modern fireplace inserts.

The recessed handle impresses with an elegant design and is completely flush with the surface. It permits easy operation and opening of the door.

For a great example of amazing function and appealing design down to the smallest detail look no further than air control lever for optimised fire control. Its design has been reduced down to basics making it unobtrusive when integrated in an appliance.

Divided glass windows made of dimensionally stable glass ceramics let you enjoy the fire without any obstructions. It is the technical innovations in the design of viewing windows that have enabled Germany's market leader Spartherm to turn a fireplace insert into an impressive, fire-based piece of art.

High efficiency, thanks to advanced technology – Spartherm's powerful fireplace inserts ensure particularly efficient operation as well as optimised use of energy. In a nutshell: Spartherm's Premium fireplace inserts are designed for sustainable use, protecting the environment and your wallet.

Spartherm use a paint system that produces a deep black surface that is scratch-free, providing a beautiful, long lasting finish. The polished glass windows have a particularly high level of transparency, making them reflection proof and resistant to soot pollution. The PremiumEdition glass doors are recessed into the fire assembly giving them a frameless profile with a seamless view of the flames, while the door handle is flush-mounted and barely visible. The surrounding cover is available in stainless steel, providing a clean and understated appearance.

regulated heat power: 5,5-10,3kW, nominal power 7,2kW;

length of firewood - 33 cm.

The corner glass is on the right side.

Door frame height 501 mm; width (side glass / facade glass): 407/554 mm.

5 year warranty for the fireplace casing.