

Heat pump air to water type Gree Versati III DUO 14,0/12,6kW



Product code: GRS-CQ14PDG-NHH-M-KO
Category: Heat pumps > Air to water heat pumps

PRICE : €7,499.99

About the product

Height, mm: 1750
Width, mm: 600
Depth, mm: 600

Description

Benefits:

- Liquid crystal display and touch-screen operation;
- integrated Wifi module
- a three-way valve, a room thermostat (temperature sensor), a water heater sensor, a signal cable between the indoor and outdoor unit, a coarse cleaning filter, a bottom heating cable for the outdoor unit are included in the set;
- integrated 185 l hot water tank;
- electrical connection - three-phase;
- working temperature in heating mode down to -25 °C, in cooling mode - from 10 to 48°C ambient temperature;
- the leaving water temperature is up to +60°C
- refrigerant circuit R32.

Values of heat pump operating parameters when T = + 7 ° C / + 35 ° C:

- rated heating power (underfloor heating): 14.0 kW;
- electricity consumption (floor heating): 2,98 kW;
- COP (underfloor heating) efficiency up to: 4,7.

Values of heat pump operating parameters when T = + 35 ° C / + 18 ° C:

- cooling capacity (floor cooling): 12,6 kW;
- electricity consumption (floor cooling): 3,41 kW;
- EER (floor cooling) efficiency up to: 3,7.

Indoor unit parameters:

- backup heating element: 3,0 + 3,0 kW - useful when the heat received from the air is not sufficient to raise the temperature of the heat carrier;
- integrated adjustable flow circulation pump;
- safety valve 1/2 ", 3bar;
- noise pressure level: 31 dB (A).